

IFJ60

Ex d IIC T6



Characteristics

Enclosure

- Aluminium LM-6 - powder coated

Standards Compliance

- IS/IEC 60079-1 : 2014
- IS/IEC 60079-0 : 2011
- IS/IEC 60529 : 2001
- Cat. No.: ILS/FA/201

Cable Entry

- M20 x 1.5 Pitch – 2 Nos.

Mounting

- Wall / STRUCTURE

Applicable Use

- Zone 1 & Zone 2
- Gas group IIA, IIB, IIC,
- Temperature class T6

Installation

- Easy installation

Weight

- 2.75 Kg

Features

- Fire & Ignition proof.
- AL die-cast LM-6 housing.
- Two earthing for better safety-internal & external.
- Neoprene gasket for trouble free long life.
- External hardware made of SS.
- Highly reliable professional design.

Description

- 10A 24/240/415 V AC/DC 50/60 Hz
- 1NO + 1 NC Contact Element
- 4 Nos 2.5sq mm Terminal Block 4 Nos.

Applications

- Chemical, paint, fertilizer industries,
- Oil & gas, refinery, petrochemicals,
- LPG bottling, pharmaceutical
- Steel, Cement industries, Mines



240V to 415V AC, 24V to 220V DC
50/60 Hz



10 Amps



Ta: -10°C to 45°C

Housing Color



Powder Coated – Red (RAL 3573)



Product Code

Product Code	Current (A)	Voltage (V)	Contact Element	Terminals	Weight (Kg)
IFJ80-10A1NO1NCRM20	10A	240/415V AC	1 NO + 1 NC	DIN Rail Mounted Connector -4 Way-2.5/4 Sqmm	2.5

Custom Order



Accessories

Optional at Extra Cost

- Double Compression Cable Gland Brass/SS – M20x1.5 Pitch
- Stopper Plug Brass/SS/MS – M20x1.5 Pitch
- Canopy – MS / GI Powder Coated / FRP Standard Paint

