

IWW10



Characteristics

Optics

- Polycarbonate Diffuser
- High transmission 90%
- Non-Removable

Thermal Interface Material

- High thermal conductivity
- Excellent heat transfer

Heat sink

- Aluminium - powder coated
- Excellent thermal conductivity

LED Driver

- Rated Supply: 240V AC, 50/60Hz
- PF > 0.95, THD <10%,
- Short circuit, open circuit,
- O/V, U/V protection

Standards Compliance

- IS 10322
- IS 15885 (Part 2/Sec 13)

Mounting

- Eye Bolt

Installation

- Easy installation

Weight

- 1.5 Kg

Cable Entry

- 1 Nos.

Housing Color




Powder Coated – Black (RAL 9005)



Powder Coated – Grey (RAL 7024)

Distribution Curve



Features

- Soft and comfortable light to relieve the fatigue of eyes.
- Excellent CRI for actual colour reproduction.
- Energy saving efficiency and low heat produce.
- AL die-cast housing for excellent heat management.
- Quick installation, special design,
- Highly reliable professional design.

Applications

- Manufacturing Unit, Ware-house,
- Airport Baggage Area,
- Parking Lot, Low Height Applications



30W / 35W / 40W / 45W



105 lm/W



6500K / 5000K / 3000K



>80



Diffused – Wide >160°



140-270V AC, 50Hz



Inventronics / Fulham / ILS



In-Built, Surge DM 4Kv CM 6Kv



Non dimmable / 1-10V / DALI




COB, Citizen / Bridgelux , SDCM <3



Ta: -10°C to 45°C



Lifespan >50000h @ L70 B50



Product Code

Product Code	System Power (W)	System Lumen (Lm)	CRI (Ra)	Color Temp (CCT)	Body Color	Beam Angle	Diming	Weight (Kg)
IWW10-030CE865GDNXX	30	3150	80	6500K	Grey	Diffused	Non-Dim	1.5
IWW10-035CE865GDNXX	35	3675	80	6500K	Grey	Diffused	Non-Dim	1.5
IWW10-040CE865GDNXX	40	4200	80	6500K	Grey	Diffused	Non-Dim	1.5
IWW10-045CE865GDNXX	45	4725	80	6500K	Grey	Diffused	Non-Dim	1.5

Custom Order



Accessories

