


IWW70



Characteristics

Optics

- Polycarbonate Diffuser
- High transmission 90%
- Non-Removable

Thermal Interface Material

- High thermal conductivity
- Excellent heat transfer

Heat sink

- Aluminium - powder coated
- Excellent thermal conductivity

LED Driver

- Rated Supply: 240V AC, 50/60Hz
- PF > 0.95, THD <10%,
- Short circuit, open circuit,
- LV cut-off, HV cut-off
- 440V AC protection 2 hrs

Standards Compliance

- IS 10322
- IS 15885 (Part 2/Sec 13)
- EN 61000-3-2, Harmonics Current
- EN 61000-3-3, Voltage Fluctuations, Flicker
- EN 61000-4-5, Surge Immunity
- EN 61547, EMC

Mounting

- Eye Bolt

Installation

- Easy installation

Weight

- 3.0 Kg

Cable Entry

- 1 Nos.

Features

- Soft and comfortable light to relieve the fatigue of eyes.
- Excellent CRI for actual colour reproduction.
- Energy saving efficiency and low heat produce.
- AL die-cast housing for excellent heat management.
- Quick installation, special design,
- Highly reliable professional design.

Applications

- Manufacturing Unit, Ware-house,
- Airport Baggage Area,
- Parking Lot, Low Height Applications

	60W / 70W
	100 lm/W
	6500K / 5700 / 5000K / 3000K
	>70
	Diffused – Wide >160°
	140-270V AC, 50Hz
	Inventronics
	In-Built, Surge DM 4Kv CM 6Kv
	Non dimmable / 1-10V / DALI
	SMD-5050, Lumiled /Osram /Bridgelux, SDCM <3
	Ta: -10°C to 45°C
	Lifespan >50000h @ L70 B50

Housing Color





Powder Coated – Black (RAL 9005)



Powder Coated – Grey (RAL 7024)

Distribution Curve



Product Code

Product Code	System Power (W)	System Lumen (Lm)	CRI (Ra)	Color Temp (CCT)	Body Color	Beam Angle	Diming	Weight (Kg)
IWW70-060SE757GDNXX	60	6000	70	5700K	Grey	Diffused	Non-Dim	3.0
IWW70-070SE757GDNXX	70	7000	70	5700K	Grey	Diffused	Non-Dim	3.0
IWW70-060SE757GDAXX	60	6000	70	5700K	Grey	Diffused	1-10V	3.0
IWW70-070SE757GDAXX	70	7000	70	5700K	Grey	Diffused	1-10V	3.0
IWW70-060SE757GDDXX	60	6000	70	5700K	Grey	Diffused	DALI	3.0
IWW70-070SE757GDDXX	70	7000	70	5700K	Grey	Diffused	DALI	3.0

Custom Order



Accessories

